

Product Presentation



Application

This machine is used for safety glove protect area and shoe upper cutting testing, but it is not suitable for the glove made of hard materials.



Principle

To cut the sample placed on the specified sample device by a spinning round cutter, make a reciprocating motion under a required loading, enclosed the auto-counted device, it has automatic stop function as soon as the testing over. To get the result by contrast the difference before and after the testing.

Safety gloves



Shoe uppers



Sample Example

Key Specification

Model	GT-KC29
Circular blade	Diameter 45±0.5mm
	Thickness 3±0.3mm
	Cutting angle 30° ~35°
Stroke	50 mm
Load	5±0.05 N
Max. Cutting Speed	10 cm/s linear speed
Counter	LCD display, 0-99,999,999
Specimen holder	2 sets
Power Supply	1 φ AC 220V 50/60HZ
Dimension (W×D×H)	51×30×34cm
Weight	57.5 kg

Standards

EN 388 section 6.2
 ISO 20344 section 6.14
 GB/T 20991 section 6.14
 AS/NZS 2210.2 section 6.14
 AQ 6102 section 4.3.2

Accessories

Standard Accessories	2set	Specimen holder
	1pc	Circular blade
	1roll	Aluminium Foil
	1pc	Filter paper
	1pc	Power line