

Product Presentation



Application

This machine is design for all kinds of textile's perspiration resistance color fastness drying test, matching GT-D09 Perspiration Tester using. It also apply for high temperature heating & drying test for other products.



Feature

- Polished stainless-steel chamber.
- Latest PID controller.
- Uniform distribution of air temperature.
- Forced-air convection.
- Double Layer glass door, larger viewing window.



Standards

Perspiration:	GB/ T 3922, AATCC 15, ISO105-E04, JIS L 0848
Sea Water:	GB/ T5714, ISO105-E02, AATCC107
Water:	GB/ T5713, ISO105 E01, AATCC106
Saliva:	GB/ T 18886

Key Specification

Model	GT-D10-30L	GT-D10-80L	GT-D10-136L	GT-D10-220L
Interior Dimensions	340*320*320mm	450*400*450mm	550*450*550mm	600*500*750mm
Chamber Volume	30L	80L	136L	220L
Temperature Range	RT+10°C~250°C			
Display Resolution	0.1°C			
Temperature Stability	±1°C			
Ambient Temperature	+5~40°C			
Power Consumption	850W	1100W	1550W	2050W
Timing Range	1~9999min			
Exterior Dimension(L×W×H)	620*530*490mm	740*618*630mm	840*670*730mm	880*720*930mm
Power Supply	1 φ AC 220V 50/60HZ			

Accessories

Standard accessories	2pcs	Shelves
	1pc	Power line